

## AIRFIELD SURVEILLANCE, SECURITY, WILDLIFE MITIGATION AND RAMP AREA MONITORING

# COMPLETE SOLUTION FOR SECURITY AND NON-COOPERATIVE SURVEILLANCE

#### **FEATURES AND BENEFITS**

Wide Beam 360° Radar – Covers the airfield like a streetlight, unlike narrow beam radars that are more like a flashlight

Advanced Camera System – Thermal imager, HD color and Network Video Recorder provide real-time assessment and forensics

Classification – The system knows the difference between people or wildlife and planes or vehicles

User Defined Rules – Incorporate location, classification, speed, size, direction and previous behavior, to reduce false alarms and only respond to real threats

## MONITORS WITH RADAR – RESPONDS WITH CAMERA AND ALARMS

Symphony ARS provides state-of-the-art protection for the entire airfield, not just the perimeter. Offered at a fraction of the cost of traditional radar technologies, Symphony ARS covers up to a mile in every direction. This ground-breaking technology improves the situational awareness and efficiency of airfield security and operations personnel.

The Symphony ARS is a turn-key delivery, which simplifies installation. Evaluated for the Federal Aviation Administration (FAA) by National Safe Skies Alliance, the Symphony ARS radar is in operation at 20 European airports and is now available in the U.S.



#### **FEATURES AND BENEFITS**

Tracking Areas – Customize tracking areas with unique parameters, rules and responses

Interfaces with Existing Systems – Provides a two-way interface with legacy airport access control and surveillance systems

24x7 remote and onsite hardware and software support

Integrated into Symphony® OpsVue™ and MobileVue® for improved situational awareness for airfield and security personnel

www.symphonycdm.com



### **About Harris Corporation**

Harris Corporation is a leading technology innovator that creates mission-critical solutions that connect, inform and protect the world. The company's advanced technology provides information and insight to customers operating in demanding environments from ocean to orbit and everywhere in between. Harris has approximately \$8 billion in annualized revenue and supports customers in 125 countries through four customer-focused business segments: Communication Systems, Space and Intelligence Systems, Electronic Systems, and Critical Networks.

## SYMPHONY AIRFIELD RADAR SYSTEM (ARS)



Thermal

Image





RADAR	ARS	ARS-X
Installation Type	Ground level slab	Rooftop to 30' elevation
Beamwidth – Elevation	3 degrees	spread beam
Beamwidth – Azimuth	1 degree	1 degree
Max Detection Range – Vehicle	5248 feet	4920 feet
Max Detection Range – Person	3280 feet	2490 feet
Max Detection Range – Wildlife	1640 feet	1245 feet
Resolution	10 inches	10 inches
Field of View	360 degrees	360 degrees
Scan Rate	216 degrees / second	216 degrees / second
Frequency		nse required in airports
CAMERA		· ·
dentification Range – Person	3280 Feet	
Visible Camera Block	36x color/mono total day/night camera	
lmager	¼" ExView HAD	
Zoom – Optical, Digital	36x, 12x	
Horizontal View Angle	2.7°(T) – 57.8°(W)	
Lens Size	3.4 – 122.4mm	
Min Day Sensitivity - Color	1.4 Lux	
Min Night Sensitivity - Mono	0.1 Lux	
nfrared Camera	FLIR core, 640x480 detector, 100mm lens, range 3280 feet	
SENSOR STAND		
Weight	172 pounds	
Height	122 inches	
Power Requirement	120 VAC, 100 VA	
Wireless Network	5GHz, 100Mbps, 10 mile range, no FCC license required	
Operating Temperature Range	-40° to +140° F, -40° to +60° C	
IP Rating	IP67	
Relay Outputs	6, Form A, 120 VAC @0.5 A or 30 VDC @ 1 A	
COMMAND & CONTROL		
Workstation	Dell Inspiron 8GB 1TB Windows 8	
Monitor	Dell UltraSharp U2412M 24-inch Widescreen Flat Panel	
Remote Monitoring	Yes, using laptop, tablet, or smartphone	
Network Video Recorder Capacity	4 TB	
Map Types	Google Earth, Aerial Photographs, Open Street Maps	
Rule Types	Approach, area, numeric, compound, history	
Behavior Assessment	Location, movement, duration, path, speed, number of rule breaks, time	
Object Classification	Yes, configurable with confidence level; Used as input to rules.	
Response Types	Follow with camera, record CCTV, audible alarm, SMS alarm, fire wildlife mitigation device, open or close gate, control warning lights	
Max Track Zones	No fixed limit	
Max Targets Tracked	No fixed limit	
Multiple ARS Stands Supported	Up to 4 per workstation, seamless integration of radar and cameras	
waitipie Aits starias supported	GPS for Blue Force Tracking, broken beam, PIR, relay input	

For more information call us toll free at 855-890-5137 or email CAS@harris.com

FLORIDA | NEW YORK | VIRGINIA | BRAZIL | UNITED KINGDOM | ABU DHABI | SINGAPORE

