



Meteorology

METEOR 700C AND 735C WEATHER RADAR

The METEOR 700C and 735C systems set the benchmark in weather radar technology and cost effectiveness. These systems are particularly suitable for meteorological services covering moderate distances and precipitation conditions in mid-latitude regions like Europe, North-America and northern Asia.

The METEOR 700C and 735C combine cutting-edge technologies with straight-forward and reliable implementation. Both METEOR C-Band systems are supplied with GDRX® 5 Digital Receiver & Signal Processor and Rainbow® 5, the most up-to-date radar software package for meteorological users. They ensure optimum data quality for the accurate measurement of rain rates, precise detection of severe weather phenomena as well as tracking and nowcasting of such events.

The METEOR 700C baseline configuration includes a 250 KW transmitter. Alternatively, the METEOR 735C boosts the peak power to more than 400 KW. It is driven by a solid-state modulator with graceful degradation providing fault-tolerant operation and higher system availability.

Both the METEOR 700C and METEOR 735C are available with single or dual polarization (DP). The dual polarization option enhances the measurement of precipitation intensity and makes way for the categorization of different types of

hydrometeor like drizzle, rain, hail and snow. Thanks to its high-powered transmitter, the METEOR 735C operates in simultaneous DP mode with almost no loss of sensitivity compared to conventional 250 KW single-polarized systems.

METEOR PRODUCT LINE ADVANTAGE

- Optimized for Rainbow® 5, the most advanced meteorological software available on the market today
- Cutting-edge 16 bit signal processor GDRX® 5
- Dynrex dual channel receiver technology for extended dynamic range
- Unattended remote operation 24 hours a day, 365 days a year
- Long-life, state-of-the-art technologies
- Full remote surveillance and control capability based on Ravis® maintenance tool
- Comprehensive BITE system
- Full network capability in heterogeneous networks
- Maximum use of COTS components (e.g. PC-based signal processing)
- Simultaneous Dual Polarization Capability available in conventional and receiver over elevation configurations

METEOR 700C / 735C SYSTEM ADVANTAGE

- High-end DWR with unparalleled price-performance ratio
- Proven magnetron technology
- Graceful degradation modulator

- EU RTTE Directive compliance due to proprietary high-power filter technology
- Minimization of lifecycle costs due to high reliability
- Improved range resolution and scanning speed through multi-trip echo recovery
- Optimized for high sensitivity in the medium to long range
- Simultaneous Dual Polarization Capability available with both systems, and with a minimum loss of sensitivity due to increased transmitter peak power in METEOR 735C



TECHNICAL DATA

SYSTEM	METEOR 700C, METEOR 735C
Mode	Doppler, Dual-Polarization
Operating Frequency Range	5430 – 5800 MHz (C-Band)
Pulse Width	0.5 – 3.5 μ s
Pulse Repetition Frequency [PRF]	250 – 2400 Hz, user selectable
Typical Operational Range / Technical Range	200 km / 600 km
Maximum Velocity	\pm 128 m/s
System Phase Stability	0.3°

ANTENNA

Type	Parabolic, prime-focus reflector with elevation-over-azimuth pedestal
Reflector Diameter	4.2 m
Minimum Gain	\geq 44.5 dBi
Maximum Half Power Beam Width	\leq 1.0°
Step Response Time for 2° step \pm 0.1°	\leq 1.0 s
Polarization	Horizontal / Horizontal and vertical
Angle Span	0° – 360° continuous in azimuth, -2° – +182° in elevation
Angular Positioning Accuracy	\pm 0.05°
Maximum AZ Scanning Speed	8 rpm
Type	Direct Drive

RADOME

Size	6.5 m
Type	Sandwich, fiberglass with foam core; quasi-random panel cut
Transmission Losses - one-way, dry surface	\leq 0.3 dB

TRANSMITTER

Type	Coaxial Magnetron with solid state, IGBT-switched modulator
Peak Power	250 KW (METEOR 700C) 400 KW (METEOR 735C)

RECEIVER

Type	Superheterodyne, dual down-conversion
Minimum Discernable Signal @ 1 MHz	\leq -114 dBm
Noise Figure	\leq 2 dB
Linear Dynamic Range @ 1 MHz	\geq 115 dB

GDRX® 5 DIGITAL RECEIVER & SIGNAL PROCESSOR

Type	Modular, multi-channel digital receiver, connected to commercial-off-the-shelf industrial PC as signal processor
Intermediate Frequency [IF]	60 MHz
IF Sampling	16 bit, 180 MHz, 6 channels
Maximum Number of Processed Range Bins	10.000 per polarization @ fully activated algorithm chain
Minimum Processing Resolution	15 m
Processing Mode	PPP, FFT/DFT, Trip recovery and filtering
Clutter Filters	IIR, DFT linear or GIP (Gaussian iterative) interpolation

Ravis® MAINTENANCE SOFTWARE

Recommended Computer Platform	Commercial Off-the-Shelf Notebook
Operating System	Linux or Windows

Rainbow® 5 METEOROLOGICAL SOFTWARE

Recommended Computer Platform	Commercial Off-the-Shelf PC
Operating System	Linux or Windows
Standard Radar Meteorological Products	PPI, MPPI, RHI, CAPPI, Pseudo-CAPPI, MCAPPI, MAX, VCUT, MVCUT, EHT
Optional Product Groups	Hydrological, Aviation, Shear, Short-Term Forecasting, Phenomena Detection, Dual-Polarization, Pre- and Post-Processing, Warning

standard values, not an absolute limitation

Selex ES GmbH

Raiffeisenstrasse 10, 41470 Neuss, Germany, Tel: +49 (0) 21 37 7 82 - 0, Fax: +49 (0) 21 37 7 82 - 11, info@selex-es-gmbh.com, www.selex-es.de

This publication is issued to provide outline information only and is supplied without liability for errors or omissions. No part of it may be reproduced or used unless authorized in writing. We reserve the right to modify or revise all or part of this document without notice.